



PinPoint GPS



Tracking technologies that deliver results

1g GPS

Now with many more locations

 **New SWIFT
Locations**

 **Standard
Locations**

Still with...

- Customisable design
- Highly flexible programming
- User recharging for repeat deployments



Map of World with Countries by FreeVectorMaps.com

Data points for illustration only

Dedicated Biologists offering specialist advice and excellent service



SIRTRACK®



PARTNERS IN TELEMETRY



PinPoint GPS



Tracking technologies that deliver results

Model Specifications

| Model | PinPoint 10 | PinPoint 50 | PinPoint 75 | PinPoint 120 | PinPoint 240 |
|--|--|-------------------|--------------------|--------------------|--------------|
| Standard weight (g) † | 1.0 | 2.0 | 3.5 | n/a | n/a |
| Heavy duty weight (g) | 1.5 | 2.2 | 4.1 | 4.8 | 10 |
| Potential number of location attempts* | | | | | |
| Number of location attempts are approximate and schedule dependent - for a better estimate for your application, contact one of our expert advisors | | | | | |
| High Intensity schedule** STANDARD FIXES | 50 | 260 | 570 | 860 | 1,700 |
| High Intensity schedule** SWIFT FIXES | 130 | 294 | 1,100 | 1,700 | 3,400 |
| Low Intensity schedule** STANDARD FIXES | 13 | 60 | 130 | 170 | 350 |
| Low Intensity schedule** SWIFT FIXES | 80 | 294 | 710 | 550 | 1,100 |
| Standard model Dimensions (l x w x h) | 21 x 13 x 5 mm | 22 x 13 x 9 mm | 25 x 13 x 10 mm | 30 x 15 x 10 mm | n/a |
| Flexible scheduling | Spread fixes over days, months or even a whole migration | | | | |
| Battery | Limited recharges, dependent on deployment | | | | |
| Operating temperature | -10°C to +35°C For temperatures below 10°C, fewer locations will be attempted | | | | |
| Antenna † | 5cm - lightweight & flexible | | | | |
| Waterproofing | Standard & Heavy duty models: Splash tolerant | | | | |
| Warranty*** | 80% of Estimated Life, to a Maximum Warranty Period of 6 months | | | | |

Please ask about other models if remote data download or a larger battery is needed.

† Tags can be further customised for attachment, antenna strength and potting level - these options will add weight.
Please contact one of our Avian Telemetry Specialists to discuss your individual project requirements.

* Locations may be attempted but the bird's behaviour can prevent GPS communication.

** High Intensity schedule calculated with 5 minute fix intervals, low intensity schedule calculated with daily fix attempts.

*** All PinPoint Tags are Warranted to be free of defects in materials and workmanship under Normal Use for a period of 80% of Estimated Life for the first deployment schedule, unless otherwise specified, to a specified Maximum Warranty Period.
The Tags should function (meaning to charge and take fixes) for the entirety of the Tag's Maximum Warranty Period.

Dedicated Biologists offering specialist advice and excellent service



SIRTRACK®



PARTNERS IN TELEMETRY

North & South America - www.lotek.com - biotelemetry@lotek.com - 001-905-836-6680

Europe, Africa & Asia - www.biotrack.co.uk - info@biotrack.co.uk - +44 (0)1929 552992

Australasia - www.sirtrack.com - sirtrack@sirtrack.com - +64 (6) 877 7736

Specifications correct as of August 2017 - SALE